

POLYFLOR BEVEL LINE STONE PUR

- Captures the natural beauty of stone
- Authentic reproductions of real materials
- Design accessories available upon request

SPECIFICATION



2.5mm



0.7mm



bevelled edge



16@ 457 x 457 = 3.34m²



4290g/m²



GENERAL PERFORMANCE

EN 649
EN ISO 10582



REACTION TO FIRE
EN 13501-1 Class Bfl-S1



ABRASION RESISTANCE
EN 649 Group T
EN ISO 10582 Type 1



SLIP RESISTANCE*
EN 13893 Class DS
DIN 51130 R10
AS/NZS 4586 R10

For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges



INDENTATION - RESIDUAL
EN 433 <0.2mm
EN ISO 24343-1 ≤ 0.05mm



DIMENSIONAL STABILITY
EN 434 <0.40%
EN ISO 23999 ≤ 0.1% max.



CASTOR CHAIR (continuous use)
EN 425 / ISO 4918 Suitable



THERMAL CONDUCTIVITY
Suitable for underfloor heating heating Max 27°C



LIGHT FASTNESS
ISO 105-B02 (Method 3) ≥6



RESPONSIBLE SOURCING
BES 6001 Very good
SA 8000 Approved factory



VOC EMISSIONS
Indoor Air Comfort GOLD - Eurofins certified product
AgBB - Very low emissions
FloorScore - Certified product



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Bevel Line PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. Bevel Line PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



Bevel Line PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS
Bevel Line PUR is ideal for all residential areas and heavy commercial areas such as hotels, offices, schools, hospitals, airports and department stores.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
At the date of issue the data presented is correct.

* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING
2011



BEVELlineTM
THE WOOD & STONE COLLECTION

STONE

POLYFLOR
PUR
POLISH FREE


PERFORMANCE AND PROPERTIES

A+BRE
ENP 429
ENVIRONMENTAL RATING

Refer to BRE Global ratings on www.greenbooklive.com



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).



POLYFLORTM
COVERING THE WORLD