

VINYL FLOORCOVERING  
WITH ENHANCED SLIP  
RESISTANCE

# Safetred Wood

## Specification

Slip resistant heavy duty printed wood effect vinyl sheet floorcovering. With Safety Clean XP PUR protection for ease of maintenance. Product Standard: EN 13845



## Make your balanced choice

Tarkett's approach to sustainability is all about giving our customers simple and clear information so they can make the right choice of flooring, balancing their project and budget requirements beside the need for sustainable solutions.

- Choose to use good materials
- Select flooring produced with fewer resources
- Ensure safer, healthier products in people-friendly spaces
- Participate in reuse and recycling of products

### Tarkett's commitments to VOC\* emissions

Currently, all floorings that Tarkett manufactures have VOC emissions of less than 100µg/m<sup>3</sup> (TVOC after 28 days) contributing to better interior air quality. This makes Tarkett an industry reference for VOC reduction with floorings that have 10 times less VOC emissions than current European standards. Our commitment to better air quality in buildings and homes is a key part of our new Balanced Choice Tag. It gives information about the content of our products and how they contribute to sustainable development enabling customers to make their balanced choice.

Classification	Standards	Safetred Wood
Type of floorcovering	EN13845	Wood effect PVC floorcovering with particle enhanced slip resistance
Classification	EN685	Commercial 34 Industrial 43
	EN13845	ESF
Technical Characteristics	Standards	Safetred Wood
Total thickness	EN 428	2.0 mm
Total weight	EN 430	3100g/m <sup>2</sup>
Form of delivery	EN 426	Rolls: 20 lm x 2m 4676 _ _ _ (3 digit colour no.)
Technical Performances	Standards	Safetred Wood
Safety Clean PUR reinforcement		Yes
Abrasion	EN13845 Annex D	<10% Particle lost
Residual indentation	EN 433	< 0.10 mm
Castor chair	EN 425	Satisfactory
Dimensional stability	EN 434	≤ 0.10%
Curl resistance to heat	EN 434	≤2mm
Flame and smoke	EN 13501-1	Bfl s1 with acrylic adhesive on concrete
	ISO 9239-1	> 9 kW/m <sup>2</sup>
Slip resistance	TRRL pendulum 4S (wet)	>36
	Surface roughness	>20µm
	DIN 51130	R10
Electrostatic properties	EN 1815	<2 kV on concrete
	EN14041	Anti Static
Impact sound reduction	EN ISO 717/2	ΔLw = 4dB
Acoustic improvement	NF S 31-074	L n,e,w = 76dB
Light fastness	EN ISO 105-B02	7
Chemical resistance	EN 423	Good resistance to everyday substances
Anti fungal treatment		Incorporates a biostat to resist fungal and bacterial growth
Thermal resistance	EN 12524	0.01 m <sup>2</sup> K/W
Underfloor heating		Suitable provided the temperature of the sub floor does not exceed 27°C
Colours		9

The above information is subject to modifications for the benefit of further improvement. (08/12). For more detailed technical information, please contact Tarkett. Follow Tarkett's installation and maintenance instructions carefully. These instructions are available on request.

**TARKETT  
BALANCED  
CHOICE**

62%  
Natural

100%  
32%  
Recyclable  
Recycled content

<100µg/m<sup>3</sup>  
Better Indoor  
Air Quality

**A+  
BRE**  
GENERIC  
ENVIRONMENTAL  
RATING

Safety floors to EN13845 have a generic A+ environmental rating in major use areas such as healthcare and education. [www.bre.co.uk/greenguide](http://www.bre.co.uk/greenguide)

EN 14041:2004  
Manufactured by  
Tarkett Ltd  
Lenham, Maidstone  
United Kingdom  
EN 13845  
Safetred Excellence  
Wood

According to European Classification EN 685

Accredited company to  
BS EN ISO 9001:2008  
BS EN ISO 14001:2004  
BS OHSAS 18001:2007



**"Improved flexibility for easy installation and handling!"**

Tarkett Limited Lenham, Maidstone, Kent ME17 2QX, United Kingdom. Tel 01622 854040 Fax 01622 854520 [www.tarkett.co.uk](http://www.tarkett.co.uk) Email: [uksales@tarkett.com](mailto:uksales@tarkett.com)



[www.tarkett.co.uk](http://www.tarkett.co.uk)

Safetred Wood 08/2012